

# SpeedMill PLUS

## Powerful and High Efficient Homogenizer

Homogenization



## SpeedMill PLUS

The SpeedMill PLUS is a highly efficient homogenization system for various starting materials used for the subsequent isolation and purification of DNA, RNA or proteins.

The homogenization process is based on an innovative mechanical principle for which a patent has been filed. This new process allows users to operate the SpeedMill PLUS continuously if necessary. The high efficiency of energy input into the sample, based on a vertical movement, procures a homogeneous disruption of the sample without destroying the target molecules.



### Homogenizer for various starting materials

- Entire and reproducible homogenizing
- Efficient sample cooling during the whole preparation
- Flexible homogenizing system for various starting materials
- Broad portfolio: open system compatible with various consumables
- Touch control panel and large display provide considerable operating convenience
- Pre-programed protocols or user-defined programming with freely selectable parameters
- Compact construction
- Can easily be operated continuously with
- No tools required to operate the instrument
- Homogenizing comparably low-noised

## SpeedMill PLUS

Powerful and High Efficient Homogenizer



## Efficient Sample Cooling

Prior, during and after preparation: For the optimized sample holder, which is used inside the SpeedMill PLUS, different temperature ratings are freely selectable due to the storage down to  $-80^{\circ}\text{C}$ .

According to this an efficient sample cooling during the whole homogenization process is warranted and the substantial sample warming that occurs with other homogenizers is prevented. The often problematic handling of liquid nitrogen or dry ice is thus a thing of the past. Additionally the considerably expense factor of this additives, which have to be loaded continuously, is not applicable. Besides the sample holder allows an easy transport of the sample tubes and a long term storage of starting or homogenized material at adequate temperatures.

**Various sample holders for several fields of applications:**



Tube Fixation for the handling of special homogenization such as mandel-based processing.



Sample Holder P20



Exchangeable sample adapters enable an easy sample handling.


## Modern Preparation of Samples: SpeedMill PLUS

The samples to be processed are rapidly and efficiently homogenized in Lysis Tubes that have been specially optimized for the system and, as such, contain different and/or application-specific beads.

Using beads makes it possible to completely and reproducibly homogenize even the toughest starting materials, such as cartilage and chitin shells of insects or ticks within a very short time. 2.0 mL and 0.5 mL containers (Lysis Tubes) with different beads can be used for sample preparation, allowing users to adapt sample processing to a diverse range of soft and hard starting materials. Operating processes, such as

### Nucleic acid extraction principle

DNA and/or RNA extraction often require the mechanical disruption of starting material. The efficient homogenization by SpeedMill PLUS creates ideal conditions for achieving the best yields of DNA and RNA while meeting highest quality requirements.



Guaranteed safety during homogenizing due to bayonet catch.

## Optimized Lysis Tubes for the Homogenizer

Achieve reliable results by running the SpeedMill PLUS with established consumables.

Established during a long-term partnership with Innuscreen GmbH a broad range of innuSPEED Lysis Tubes suitable for diverse kinds of starting materials have been validated.

- Ideal for mechanical disruption of a very large variety of starting materials
- Fast, efficient preparation of robust samples for isolating nucleic acids or proteins
- 0.5 or 2.0 mL reaction vessels with beads
- Flexibility thanks to a variety of bead materials and sizes
- Ideal for use with the SpeedMill or other commercially available homogenizers

innuSPEED lysis tubes include a variety of 0.5 and 2.0 mL reaction vessels with skirted bases and screw caps. Prefilled with beads in various sizes, materials and quantities, innuSPEED lysis tubes are ideally suited for homogenizing an exceptionally wide variety of starting materials (e.g., plants, tissues, cells, etc.). As a general rule of thumb: the smaller the sample, the smaller the beads.

For more information on the innuSPEED Lysis Tubes please contact Innuscreen GmbH.

A wide range of different kinds of Lysis Tubes with application specific beads for an effective homogenization



## Technical Data

System parameters	
Homogenization time	30 sec to 4 min (depending on the starting material)
Device handling	Stand-alone device, simple starting and handling of device by using modern touch sensors
Acceleration time	No acceleration
Deceleration time	No deceleration
Application parameters	
Homogenization routines	User-defined programming with user-defined parameters, as well as pre-programmed protocols
Sample handling	Simple sample tube loading and removal
Sample capacity	Up to 20 samples simultaneously
Sample cooling	Passive cooled sample holder; storage at temperatures down to -80 °C
Programming parameters	
Homogenization time range	1 sec to 4:59 min
Steps of adjusting time	1 sec
Pre-programmed protocols	Yes
User-defined protocols	Yes
Storable protocols	20
Number of cycles	1 – 99
Protocol steps	1 – 6
Accessories	
Lysis Tubes	Broad ranged portfolio of chooseable Lysis Tubes with various volumina and beads
Complete purification	innuSPEED Kits containing Lysis Tubes for standardized starting materials enable effective extraction of nucleic acids without previous homogenizing optimization
Other technical data	
Dimensions (W × H × D)	154 × 275 × 257 mm
Weight	12 kg
Power Supply	AC 220 V, 50 Hz/110 V, 60 Hz
Power consumption	150 W (max)
Warranty	2 years

# Order Information

Order number	Description
845-00007-2	<b>SpeedMill PLUS</b> 220 V stand-alone instrument system, including Sample Holder P20 (passive cooling function, 20 positions, aluminium, black)
845-00007-4	<b>SpeedMill PLUS</b> 110 V stand-alone instrument system, including Sample Holder P20 (passive cooling function, 20 positions, aluminium, black)
845-60053-0	<b>Sample Holder P20</b> Sample Holder in aluminium design (black) for up to 20 sample, passive cooling function and storage down to -80 °C
845-60054-0	<b>Tube Fixation</b> Lock to fix Lysis Tubes, optimized for usage of innuSPEED Lysis Tube Q (mandrel)

innuSPEED Lysis Tubes are available via Innuscreen GmbH. For more information please contact [info.innu@ist-ag.com](mailto:info.innu@ist-ag.com).

## Headquarters

Analytik Jena GmbH  
Konrad-Zuse-Str. 1  
07745 Jena · Germany

Phone +49 3641 77 70  
Fax +49 3641 77 9279  
[info@analytik-jena.com](mailto:info@analytik-jena.com)  
[www.analytik-jena.com](http://www.analytik-jena.com)

Pictures: Analytik Jena GmbH  
Subject to changes in design and scope of delivery as well as further technical development.